

NT CAT A-4 Catalyst CAS8001-28-0 Newtopchem

NT CAT A-4 is a quick-acting catalyst used in the production of polyurethane foams. It is a water-based catalyst that is compatible with a variety of polyurethane systems. NT CAT A-4 is also non-corrosive and non-flammable.

NT CAT A-4 is a popular choice for a variety of polyurethane applications, including:

Soft foam

Hard foam

Spray foam

Molding plastic

Elastomer

Paint

NT CAT A-4 is a safe and effective catalyst for polyurethane foam production. Always follow the manufacturer's instructions when using NT CAT A-4 to ensure safe and effective use.



Here is some additional information about NT CAT A-4:

- NT CAT A-4 is a tertiary amine. A tertiary amine is an organic compound containing three nitrogen atoms. Tertiary amines are often used as catalysts in chemical reactions.
- NT CAT A-4 is a water-based catalyst. Water-based catalysts are generally superior to organic solvents because they are non-flammable and less toxic.
- NT CAT A-4 is compatible with a variety of polyurethane systems. This means that it can be used to produce a variety of polyurethane foams, including soft foams, hard foams, spray foams, molded plastics, elastomers, and coatings.
- NT CAT A-4 is a safe and effective catalyst. Always follow the manufacturer's instructions when using NT CAT A-4 to ensure safe and effective use.

How does the NT CAT A-4 work?

NT CAT A-4 works by catalyzing the reaction between isocyanates and polyols. The reaction produces polyurethane foam, a versatile material with a wide range of uses.

Benefits of using NT CAT A-4

There are many benefits to using NT CAT A-4, including:

- Quick-acting catalyst
- Compatible with a wide range of polyurethane systems
- Non-corrosive and non-flammable
- Safe and effective

Application of NT CAT A-4

NT CAT A-4 is a versatile catalyst that can be used in a wide range of polyurethane applications, including:

- Soft foams
- Hard foam
- Spray foam
- Molding plastic

- Elastomer
- Paint

Safety information

NT CAT A-4 is a hazardous substance. It is very important to read and understand the safety information before using NT CAT A-4. Some important safety information includes:

- NT CAT A-4 is a skin irritant. Avoid contact with your skin.
- NT CAT A-4 is a respiratory irritant. Avoid inhaling vapors or fumes.
- NT CAT A-4 is a flammable liquid. Keep away from heat sources and open flames.
- NT CAT A-4 is a toxic substance. Do not swallow.

If you come into contact with NT CAT A-4, wash the affected area with soap and water immediately. If you inhale NT CAT A-4 vapor or mist, move to fresh air and seek medical attention if you develop any symptoms. If you swallow NT CAT A-4, call the poison control center immediately.

Storage and disposal

NT CAT A-4 should be stored in a cool, dry place. Keep away from heat sources and open flames. NT CAT A-4 should be disposed of in accordance with local, state, and federal regulations.

CONCLUSION

NT CAT A-4 is a fast acting catalyst for the production of polyurethane foam. It is a water-based catalyst that is compatible with a variety of polyurethane systems. NT CAT A-4 is also non-corrosive and non-flammable. NT CAT A-4 is a safe and effective catalyst for polyurethane foam production. Always follow the manufacturer's instructions when using NT CAT A-4 to ensure safe and effective use.

Shelf life:

Remain unopened for two years

Storage and Transportation:

Should be sealed, stored in a dry cool ventilated warehouse

Packing:

200KG/ barrel storage: It is recommended to store in a dry and cool area with proper ventilation. After the original packaging, please fasten the packaging cover as soon as possible to prevent moisture and other substances from mixing and affecting the

product performance. Do not inhale dust and avoid contact between skin and mucous membrane. Smoking, eating and drinking are prohibited in the workplace. Shower and change after work. Store contaminated clothes separately and use them after washing. Practice good hygiene.

Technical support and business contacts E-mail: info@newtopchem.com