

NT CAT T26 catalyst CAS11207-74-9 Newtopchem

NT CAT T26 is a stannous caprylate catalyst used in the production of polyurethane foams. It is a clear, colorless liquid with a mild odor. NT CAT T26 is compatible with many polyols and isocyanates. It is also non-corrosive and non-flammable.

Physical and chemical properties

| Properties | Value |
|-------------------|---|
| CAS number | 11207-74-9 |
| Molecular Formula | C ₁₂ H ₂₂ O ₈ Sn |
| Molecular weight | 364.43 g/mole |
| Appearance | Clear colorless liquid |
| Specific gravity | 1.065 @ 25°C |
| Refractive Index | 1.495 @ 25°C |

| | |
|------------------------------------|--|
| Solubility | Dissolve in most organic solvents |
| Flash Point | 57°C (135°F) |
| Spontaneous combustion temperature | 725°F (390°C) |
| Stable | Stable under normal storage conditions |
| Hazards | <p>Corrosive to skin and eyes. May be harmful if swallowed. The steam may irritate the eyes, nose and throat. May cause respiratory irritation. May be harmful if inhaled. May cause skin irritation.</p> <p>May be harmful if swallowed. First aid: In case of contact with skin, wash immediately with soap and water. If contact is made with eyes, immediately rinse with water for 15 minutes and seek medical attention. If swallowed, do not try to induce vomiting. Call poison control or seek medical attention immediately.</p> |

Apply

NT CAT T26 is used in a variety of polyurethane foam applications, including:

Rigid foams

Soft foam

Spray foam

In-situ foam

Elastomer

Paint

Ink

Adhesive



Precautions for use

Newtop Chemical Materials (Shanghai) Co.,Ltd.

Address: Rm1104 ,No. 258, West SongXing Road, BaoShan District, Shanghai, China.

Mobile Phone: +0086-183 0190 3151 E-mail: info@newtopchem.com www.newtopchem.com

NT CAT T26 is a hazardous material and should be handled with care. Always follow the manufacturer's instructions when using a NT CAT T26.

Storage

Store in a cool, dry place. Keep out of reach of children and pets.

Disposal

Dispose in accordance with local, state, and federal regulations.

Additional Information

NT CAT T26 is a versatile catalyst that can be used in a variety of polyurethane foam applications. It is non-corrosive and non-flammable, making it a safe and easy to use product. NT CAT T26 is also compatible with a wide range of polyols and isocyanates, making it a versatile choice for foam producers.

Here are some additional benefits of using NT CAT T26:

- It produces high quality foam with good physical properties.
- It is cost effective and easy to use.
- It is safe and non-toxic.

If you are looking for a high quality, versatile and safe catalyst for your polyurethane foam application, NT CAT T26 is a good choice.

Shelf life:

Remain unopened for two years

Storage and Transportation:

Should be sealed, stored in a dry cool ventilated warehouse

Packing:

200KG/ barrel storage: It is recommended to store in a dry and cool area with proper ventilation. After the original packaging, please fasten the packaging cover as soon as possible to prevent moisture and other substances from mixing and affecting the product performance. Do not inhale dust and avoid contact between skin and mucous membrane. Smoking, eating and drinking are prohibited in the workplace. Shower and change after work. Store contaminated clothes separately and use them after washing. Practice good hygiene.

Technical support and business contacts E-mail: info@newtopchem.com